

EVEREST

EVEREST SNOWBLOWERS



EVEREST SNOWBLOWERS




Everest snowblowers have been designed and built with quality and durability to meet all your snow clearing needs.

With a range of sizes for 14hp - 125hp tractors there will be one to fit your tractor.

All Everest Snowblowers are Quick Hitch compatible which makes for ease of attachment.

Shear bolts protect both the PTO driveline and the auger drive from unforeseen foreign objects or overload.

1. All models feature a 3 position adjustable hitch for ease of attachment.
2. Replaceable cutting edge is standard on 6096 & 6108L models.
3. Manual spout rotator is standard on the 6054 - 6084 models.
4. The integrated hydraulic spout rotator on the 6096 & 6108L models makes efficient use of your hydraulic power available. Optional for 6054 - 6084 models.
5. 6 position adjustable skid shoes allow for precise height setting of the cutting edge. Parking jack is standard on all models.
6. Manual spout deflector is standard on 6054 - 6084 models. Hydraulic deflector kit is standard on the 6108L and 6096 model and optional on all other models.
7. - Tough cast flange bearings are used for increased strength and less maintenance.
- Whether your snow is light and fluffy, or dense and compacted, the 4-blade fan is the perfect medium to get the job done.
- Replaceable Cutting Edge Standard on all models.



Model	6054	6060	6072	6084	6096	6108L
Cutting Width	56.5"	62.5"	75"	87"	98.5"	111"
Cutting Height	25.5"	28"	29.5"	30"	40"	40"
Replaceable Cutting Edge	Standard	Standard	Standard	Standard	Standard	Standard
Fan	4 Blade	4 Blade	4 Blade	4 Blade	4 Blade	4 Blade
Fan Diameter	20"	22"	24"	24"	32"	32"
Fan Driver	540 rpm - gearbox	540 rpm - gearbox	540 rpm - gearbox	540 rpm - gearbox	540 rpm - gearbox	540 rpm - gearbox
Auger Diameter	13" - single	15" - single	15" - single	15" - single	15" - double	15" - double
Auger Drive	#50 chain	#60 chain	#60 chain	#60 chain	#60H chain	#60H chain
Body	14 GA	12 GA	10 GA	10 GA	7 GA	7 GA
Side Plates	12 GA reinforced	10 GA reinforced	10 GA reinforced	10 GA reinforced	7 GA reinforced	7 GA reinforced
Spout Rotator						
- manual (handcrank)	Standard	Standard	Standard	Standard		
- hydraulic	Optional	Optional	Optional	Optional	Standard	Standard
Spout Deflector						
- manual (6 position)	Standard	Standard	Standard	Standard		
- hydraulic	Optional	Optional	Optional	Optional	Standard	Standard
Skid Shoes	Standard - adj.	Standard - adj.	Standard - adj.	Standard - adj.	Standard - adj.	Standard - adj.
Hitch Category Standard,	Cat. 0 & Cat. 1	Cat. 1	Cat. 1 & Cat. 2	Cat. 1 & 2	Cat. 2 & 3	Cat. 2 & 3
Hitch Adjustment	3 Position	3 Position	3 Position	3 Position	3 Position	3 Position
HP Recommended	14 - 25	18 - 40	35 - 75	45-90	90-125	90-125
Custom Colours	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Weight	345#	535#	645#	720#	1540#	1675#

Specifications subject to change



Winkler, MB
Ph. (204) 325-9374
Toll Free 1-866-325-9374
Email: sales@generalmetal.ca
www.generalmetal.ca

Your Local Dealer is