

# ***BAU-MAN***

**POTATO HANDLING & TRANSPORTATION EQUIPMENT**

**STRAIGHT & TELESCOPING CONVEYORS**



***BAU-MAN* . . . Built to be Better**

**QUALITY • DEPENDABLE • PROVEN**

# STRAIGHT & TELESCOPING CONVEYORS

Designed for ease of use, all **BAU-MAN** conveyors feature adjustable tow hitch and sealed greaseable bearings in heavy load areas.

Crowned roller assemblies improve belt tracking and are designed to improve self-cleaning.

The simple robust belt tightening system means your 2 ply rubber belt is easy to adjust and will perform year after year, with regular maintenance.

Height adjustment of 10" or 15" on straight, and 9" on telescoping conveyors allows you to match your conveyor to a variety of height requirements. The castoring wheels add maneuverability to the straight conveyors.

## Optional Features:

- Trough belt design - Eliminate Potato's rubbing on Conveyor sides
- Interlocking electrical control
- Butt together style or hopper style
- Hydraulic wheel drive and steering



STRAIGHT & TELESCOPING CONVEYORS							
Please contact us for custom sizes not listed							
Conveyor Series	1630	1640	1650	1450	1460	1475	1485
Length Retracted	30'	40'	50'	32'	38'	46'	51'
Length Extended	30'	40'	50'	50'	60'	75'	85'
Belt Width	30"/36"/42"	30"/36"/42"	30"/36"/42"	30"/36"/42"	30"/36"/42"	30"/36"/42"	30"/36"/42"
Tires	12"	12"	12"	15"	15"	15"	15"w/15" centre support wheels
Discharge Height (min)*	29"	29"	29"	32"	32"	32"	32"
Discharge Height (max)*	45"	45"	45"	41"	41"	41"	49"
Capacity, tons/hr **	225/250/275	225/250/275	225/250/275	225/250/275	225/250/275	225/250/275	225/250/275
Telescoping	No	No	No	Yes	Yes	Yes	Yes
Pivoting	No	No	No	Opt.	Opt.	Opt.	Opt.
Horsepower	3	5	5	2 x 3 HP	2 x 3 HP	2 x 5 HP	2 x 5 HP
Motor Mount	Top std. Bottom opt.	Top std. Bottom opt.	Top std. Bottom opt.	Top std.	Top std.	Top std.	Top std.
Electrical Control	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.	Manual shut-off, Automatic opt.
Hyd. Wheel Drive & Steering	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
*Measurement to bottom of belt, extended.	** Estimated	Specs subject to change without notice.					



**Winkler, MB**  
 Ph. (204) 325-9374  
 Toll Free 1-866-325-9374  
 Email: sales@generalmetal.ca  
 www.generalmetal.ca

**Your Local Dealer is**