EHERESI

EVEREST FINISHING MOVVER



optional colour



EVEREST FINISHING MOVVER

Everest Finishing Mowers are the development of years of combined experience in the grass cutting industry. These Finishing Mowers feature top quality construction and only the best performance you have come to expect on your acreage. Everest mowers are North American made with uncompromising strength and durability. An extremely high blade tip speed and blade overlap prevent stripping and ensures quality finish second to none.

STANDARD FEATURES:

- The robust and rugged gearbox is the heart of the mower. The single belt adjustment reduces maintenance time. (5)
- Pneumatic tires with puncture resistant sealant (1)
- Oil soaked wheel bushings ensure reliability with less maintenance. (6)
- Alloy hardened high speed blades with tungsten hard surfacing. (opt on 5 & 6', standard on 7')
- Large blade mounting area for added strength
- Locking compound used to fasten blades to spindles
- Large diameter sealed blade spindles for zero maintenance. (4)
- Fully height adjustable wheel yoke assemblies (6) (see matrix for details)
- Fully floating hitch keeps the deck level to the ground for a crisp even cut. (2)







EVEREST FINISHING MOWER

<u>Model</u>	<u>5500</u>	<u>5600</u>	<u>5700</u>
Cutting Width	60"	72"	84"
Deck Material	7 gauge	7 gauge	7 gauge
Gearbox	Sealed, oil bath (540 RPM)	Sealed, oil bath (540 RPM)	Sealed, oil bath (540 RPM)
Hitch	Cat. 1, QH adaptable	Cat. 1, QH adaptable	Cat. 1, QH adaptable
Blade tip speed	15829 ft. / min.	18737 ft. / min.	18552 ft. / min.
Blade material	1/4" x 2 ½" alloy hardened	1/4" x 2 ½" alloy hardened	1/4" x 3" alloy hardened
Blade length	21 3/4"	25 3/4"	29 3/4"
Blade overlap	2 5/8"	2 5/8"	2 5/8"
Blades	3	3	3
Drive	2 belt, "B" groove	2 belt, "B" groove	2 belt, "B" groove
Cutting height	1 ½" x 4 ½"	1 ½" x 4 ½"	1 ½" x 4 ½"
Spindles	3 cast w/bearings	3 cast w/bearings	3 cast w/bearings
Front roller	4" x 5 3/8"	4" x 5 3/8"	4" x 5 3/8"
Tires	4.10 / 3.50 - 4	4.10 / 3.50 - 4	13 x 5.0 x 6
Quick hitch adaptor	Opt.	Opt.	Opt.
Min. recommended HP	15	20	25
Weight (lbs)	560	625	730



Winkler, MB Ph. (204) 325-9374 Fax (204) 325-5175 Toll Free 1-866-325-9374 www.generalmetal.ca **Your Local Dealer is**